



MVC




Request/Response Lifecycle

1. **Request** - link pressed on page
2. **Router** - find matching controller object
3. **Controller** - method invoked to handle request
4. **View** - data sent from controller to view to construct response
5. **Response** - complete page rendered into browser


Router/Controller/View




Router/Controller/View




Router/Controller/View




Router/Controller/View




Router/Controller/View



Router/Controller/View




Router/Controller/View




Request - link pressed on page

```
...  
  <a id="dashboard" class="item" href="/dashboard"> Dashboard </a>  
  <a id="about" class="item" href="/about"> About </a>  
...
```

- Requests defined in links in views:
 - href in <a> tags
 - href in Menus
 - href in Buttons
 - action links in forms



Router - find matching controller object



routes

Mach the link patterns with the controller.method


...		
GET	/	Start.index
GET	/dashboard	Dashboard.index
GET	/about	About.index
...		

Router Behaviour

If user selects
these links...

' / ' → Start.index
/dashboard → Dashboard.index
/about → About.index

...then call the
corresponding
controller
methods



Controller method invoked to handle request



About.java

```
package controllers;

import play.*;
import play.mvc.*;
import java.util.*;
import models.*;

public class About extends Controller
{
    public static void index() {
        Logger.info("Rendering about");
        render ("about.html");
    }
}
```

The About controller




The ‘About’ controller index action

```
public static void index() {  
    Logger.info("Rendering about");  
    render ("about.html");  
}
```

```
12:28:42,071 INFO ~ Application playlist is not  
12:28:42,127 INFO ~ Rendering Dashboard  
12:28:44,618 INFO ~ Rendering about  
12:28:45,193 INFO ~ Rendering Dashboard  
12:28:46,233 INFO ~ Rendering Start  
12:28:47,233 INFO ~ Rendering Dashboard  
12:29:18,611 INFO ~ Rendering Dashboard  
12:29:46,311 INFO ~ Rendering about  
12:29:47,111 INFO ~ Rendering Dashboard  
12:29:48,199 INFO ~ Rendering Start  
[]
```

Log a message
to the console



Render the ‘about’ view

about.js


Back-end + Front-End

```
public static void index() {  
    Logger.info("Rendering about");  
    render ("about.html");  
}
```

```
#{extends 'main.html' /}  
#{set title:'About' /}  
  
#{menu id:"about"/}  
  
<section class="ui center aligned middle aligned segment">  
    <p>  
        About this app  
    </p>  
</section>
```



menu.html




main.html

```
<nav class="ui menu">  
    <header class="ui header item"> <a href="/"> Template 1 </a></header>  
    <div class="right menu">  
        <a id="dashboard" class="item" href="/dashboard"> Dashboard </a>  
        <a id="about" class="item" href="/about"> About </a>  
    </div>  
</nav>  
  
<script>  
    $("#${_id}").addClass("active item");  
</script>
```

```
<!DOCTYPE html>  
<html>  
    <head>  
        <title>#{get 'title' /}</title>  
        <script type="text/javascript" src="https://cdnjs.cloudflare.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>  
        <script type="text/javascript" src="https://cdnjs.cloudflare.com/ajax/libs/semantic-ui/2.4.1/semantic.min.js"></script>  
        <link type="text/css" href="https://cdnjs.cloudflare.com/ajax/libs/semantic-ui/2.4.1/semantic.min.css"/>  
    </head>  
    <body>  
        <section class="ui container">  
            #{doLayout /}  
        </section>  
    </body>
```

Router/Controller/View



Router/Controller/Model/View

